

## RIDEMAX FL 615 - Spécifications techniques



### Description

RIDEMAX FL 615 est un pneu à flottaison radiale convient pour les essieux tirés des remorques, citernes et épandeurs. La structure avec ceintures d'acier offre une résistance élevée à la perforation ainsi qu'une durabilité accrue et une capacité de charge élevée. RIDEMAX FL 615 assure une faible résistance au roulement sur la route avec des propriétés autonettoyantes exceptionnelles dans les champs. Son épaulement arrondi et la large zone d'empreinte offrent une grande protection du sol.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

Version	STEEL BELTED
Type	TL
Tyre Size	800/65 R 32
LI/SS	185 D
LI/SS DRIVE WHEEL	185 D
LI/SS FREE ROLLING	185 D

## Dimensions International Standard

Section Width (mm)	830
Overall Diameter (mm)	1853
Static Loaded Radius (mm)	834
Rolling Circumference (mm)	5624
SRI (mm)	875
Rim Rec	DW 27 B
ECE	E11-106R-007528

## Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6
65	3980	4350	5275	5830	6755	7680	8420	9250
50	4815	5265	6385	7055	8175	9295	10190	11195
40	5410	5915	7175	7930	9185	10445	11450	12580
30	6010	6570	7965	8805	10200	11600	12715	13970
25	6285	6870	8335	9210	10670	12135	13300	14615
10	7160	7830	9495	10490	12155	13820	15155	16650

Printed on 26/04/2024 12:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..