

RIDEMAX FL 615 - Fiche de données



Description

RIDEMAX FL 615 est un pneu à flottaison radiale convient pour les essieux tirés des remorques, citernes et épandeurs. La structure avec ceintures d'acier offre une résistance élevée à la perforation ainsi qu'une durabilité accrue et une capacité de charge élevée. RIDEMAX FL 615 assure une faible résistance au roulement sur la route avec des propriétés autonettoyantes exceptionnelles dans les champs. Son épaulement arrondi et la large zone d'empreinte offrent une grande protection du sol.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Épandeur • Véhicule citerne • Remorque

SIZE	Version	USACode	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
800/65 R 32	STEEL BELTED	94070176	185 D	185 D	185 D	DW 27 B		32.7	73	32.8	221.4	TL	E11-106R-007528

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 12:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..