

## RIDEMAX FL 690 - Spécifications techniques



### Description

RIDEMAX FL 690 est un pneu radial Flotation et de transport bien adapté pour les camions-citernes et les remorques. Le pneu a été conçu pour les applications 75% sur route. Pour répondre à la demande pour des charges toujours plus lourdes dans l'agriculture moderne, BKT a réalisé ce pneu avec des ceintures d'acier qui confèrent une capacité de charge élevée, en augmentent la productivité de l'agriculteur. La résistance au roulement réduite contribue à l'économie de carburant.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque  
Industriel: Remorque

Version	STANDARD
Type	TL
Tyre Size	28L R 26 (750/65 R 26)
LI/SS	176 A8/173 B

## Dimensions US Standard

Usa code	94034321
Section Width (inch)	28.3
Overall Diameter (inch)	62.6
Static Loaded Radius (inch)	27.4
Rolling Circumference (inch)	186.8
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-002985

## Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41
30	6880	7850	9530	10320	11750	13040	14330
25	7520	8560	10420	11280	12840	14250	15650
20	8420	9600	11670	12630	14380	15960	17540
15	8950	10200	12390	13410	15280	16950	18630
5	10530	11990	14580	15780	17980	19950	21910

Printed on 23/04/2024 11:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..