

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	425/55 R17
LI/SS	129 D/140 A8

Dimensions US Standard

Usa code	94059324
Section Width (inch)	16.5
Overall Diameter (inch)	35.2
Static Loaded Radius (inch)	15.6
Rolling Circumference (inch)	106.5
Rim Rec	13.00
ECE	E11-106R-005104

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
40	1310	1680	2080	2370	2730	3110	3390	3710	4080
30	1590	2030	2520	2870	3320	3760	4100	4500	4940
25	1760	2260	2810	3200	3690	4190	4570	5020	5510
20	1970	2540	3150	3580	4130	4680	5110	5610	6160
15	2070	2650	3300	3750	4320	4910	5360	5870	6450
5	2360	3020	3750	4270	4930	5590	6100	6690	7340

Printed on 07/12/2023 21:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..