

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	560/45 R 22.5
LI/SS	152 D/149 E

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1076
Static Loaded Radius (mm)	491
Rolling Circumference (mm)	3306
SRI (mm)	525
Rim Rec	AG 16.00
ECE	E4-106R-000629

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1205	1365	1625	1920	2195	2440	2730	2990	3250
65	1320	1495	1775	2095	2400	2665	2985	3270	3550
50	1595	1810	2150	2540	2905	3225	3615	3960	4300
40	1790	2030	2415	2850	3265	3625	4060	4445	4830
25	2080	2360	2805	3310	3790	4210	4715	5165	5610
10	2365	2685	3195	3775	4315	4795	5370	5880	6390

Printed on 02/10/2023 21:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..