

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	169 D

## Dimensions US Standard

Usa code	94037537
Section Width (inch)	25.4
Overall Diameter (inch)	54.7
Static Loaded Radius (inch)	24.4
Rolling Circumference (inch)	166
Rim Rec	AG 20.00
ECE	E4-106R-000806

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	4330	4920	5960	6900	7950	9010	9700	10760	11680
40	4740	5380	6530	7550	8700	9850	10610	11770	12790
30	5730	6500	7900	9140	10530	11930	12850	14240	15480
25	6440	7310	8870	10270	11840	13400	14440	16000	17390
15	7480	8490	10310	11930	13750	15560	16780	18590	20200
5	8520	9670	11740	13580	15650	17720	19110	21170	23010

Printed on 07/12/2023 21:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..