

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	710/45 R 22.5
LI/SS	165 D

## Dimensions US Standard

Usa code	94062447
Section Width (inch)	27.8
Overall Diameter (inch)	47.7
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	144
Rim Rec	AG 24.00
ECE	E11-106R-005994

## Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3780	4240	5270	6000	6920	7860	8580	9400	10330
40	4140	4660	5800	6590	7620	8630	9420	10340	11350
30	5030	5640	7010	7980	9210	10450	11420	12510	13750
25	5640	6340	7880	8960	10350	11740	12820	14050	15440
20	6260	7030	8750	9950	11500	13040	14240	15610	17150
15	6560	7360	9160	10420	12030	13650	14900	16340	17940
5	7460	8390	10430	11860	13700	15540	16960	18610	20440

Printed on 27/04/2024 16:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..