

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	VF 400/45 R 17.5
LI/SS	142 D

Dimensions US Standard

Usa code	94069323
Section Width (inch)	15.7
Overall Diameter (inch)	31.5
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	96.4
Rim Rec	14.00
ECE	E11-106R-007199

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
45	2290	2780	3100	3570	4060	4420	4850	5320
40	2510	3040	3390	3920	4440	4850	5320	5840
30	3050	3680	4110	4750	5380	5870	6450	7080
25	3430	4130	4620	5330	6040	6600	7240	7950
20	3800	4600	5130	5920	6710	7330	8040	8830
15	3980	4810	5370	6190	7020	7670	8410	9240
5	4530	5480	6110	7050	8000	8730	9580	10520

Printed on 07/12/2023 21:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..