

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	VF 500/50 R 17
LI/SS	156 D

Dimensions US Standard

Usa code	94069453
Section Width (inch)	19.8
Overall Diameter (inch)	36.7
Static Loaded Radius (inch)	16.6
Rolling Circumference (inch)	113.4
Rim Rec	16.00
ECE	E11-106R-007200

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	65	73
45	2420	3060	3700	4110	4740	5380	5950	6510	7150	7630	8030
40	2650	3360	4060	4500	5210	5910	6530	7150	7850	8380	8820
30	3210	4060	4920	5450	6310	7160	7910	8660	9510	10150	10670
25	3610	4570	5530	6120	7080	8040	8890	9730	10690	11400	12000
15	4190	5310	6420	7110	8230	9340	10320	11290	12410	13240	13940
5	4770	6050	7310	8110	9370	10640	11750	12870	14140	15080	15880

Printed on 07/12/2023 22:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..