

## RIDEMAX FL 693 M - Fiche de données



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
425/55 R17	STANDARD	94059324	129 D/140 A8	13.00		16.5	35.2	15.6	106.5	TL	E11-106R-005104
500/50 R 17	STANDARD	94045181	149 D/146 E	16.00		19.8	36.7	16.7	114.7	TL	E4-106R-001821
VF 500/50 R 17	STANDARD	94069453	156 D	16.00		19.8	36.7	16.6	113.4	TL	E11-106R-007200
400/45 R 17.5	STANDARD	94066063	139 D	14.00		15.7	31.5	13.5	92.8	TL	E11-106R-006619
VF 400/45 R 17.5	STANDARD	94069323	142 D	14.00		15.7	31.5	14.1	96.4	TL	E11-106R-007199
500/45 R 22.5	STANDARD	94043767	146 D/143 E	AG 16.00		19.8	40.2	17.9	122.6	TL	E4-106R-000786
500/60 R 22.5	STANDARD	94069446	163 D	AG 16.00	15.00 ; 17.00	19.8	46.1	21.4	142.7	TL	E11-106R-007203
500/60 R 22.5	STANDARD	94040605	155 D/152 E	AG 16.00	15.00 ; 17.00	19.8	46.1	20.9	140.8	TL	E4-106R-001402
560/45 R 22.5	STANDARD	94037322	152 D/149 E	AG 16.00		21.4	42.4	19.3	130.2	TL	E4-106R-000629
560/55 R 22.5	STANDARD	94067626	162 D	AG 16.00	17.00 ; 20.00	21.4	46.5	21	142.3	TL	E11-106R-006972
560/55 R 22.5	STANDARD	94037353	158 D/155 E	AG 16.00	17.00 ; 20.00	21.4	46.5	21	142.3	TL	E4-106R-000631
560/60 R 22.5	STANDARD	94066193	169 D	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49	21.7	148.3	TL	E11-106R-006650
560/60 R 22.5	STANDARD	94037247	161 D/158 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49	21.6	148.3	TL	E4-106R-000630
560/60 R 22.5	STANDARD	94045891	165 D/162 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49	21.7	148.3	TL	E4-106R-001403
580/65 R 22.5	STANDARD	94037254	166 D/163 E	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	22.7	52.2	22.5	158.7	TL	E4-106R-000804
600/50 R 22.5	STANDARD	94037032	159 D/156 E	AG 20.00		24.1	46.1	20.3	140.7	TL	E4-106R-000805
650/50 R 22.5	STANDARD	94043019	163 D/160 E	AG 20.00		25.4	48.1	21.1	146.3	TL	E4-106R-001417
650/50 R 22.5	STANDARD	94055654	168 D	AG 20.00		25.4	48.1	21.1	146.3	TL	E11-106R-006489
710/35 R 22.5	STANDARD	94056132	157 D/154 E	AG 24.00		28	42.1	19	128.1	TL	E11-106R-004758
710/45 R 22.5	STANDARD	94062447	165 D	AG 24.00		27.8	47.7	21.3	144	TL	E11-106R-005994
600/55 R 26.5	HD	94049615	177 D	AG 20.00		24.1	52.5	23.1	160.5	TL	E11-106R-003007
600/55 R 26.5	STANDARD	94047277	165 D	AG 20.00		24.1	52.5	23.1	159.5	TL	E4-106R-002398
650/55 R 26.5	HD	94049622	178 D	AG 20.00		25.4	54.7	24.2	167.3	TL	E11-106R-003008
650/55 R 26.5	STANDARD	94037537	169 D	AG 20.00		25.4	54.7	24.4	166	TL	E4-106R-000806
710/50 R 26.5	HD	94063673	179 D	AG 24.00	AG 20.00	28.6	54.4	23.9	166	TL	E11-106R-006008
710/50 R 26.5	STANDARD	94037315	170 D	AG 24.00	AG 20.00	28.6	54.4	24.6	166	TL	E4-106R-001422
600/60 R 30.5	STANDARD	94064335	169 D	AG 20.00	AG 18.00	23.8	58.9	26.8	177	TL	E11-106R-006160
600/60 R 30.5	STANDARD	94069330	173 D	AG 20.00	AG 18.00	23.8	58.9	26.8	177	TL	E11-106R-007198
710/50 R 30.5	STANDARD	94037049	173 D	AG 24.00	AG 20.00	28.6	58.5	26.6	178.5	TL	E4-106R-001498
750/60 R 30.5	STANDARD	94033812	181 D	AG 24.00		29.7	65.9	28.7	200.5	TL	E4-106R-001499

Printed on 07/12/2023 20:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..