

## ROCK GRIP E4 - Spécifications techniques



### Description

ROCK GRIP (E-4) est un pneu à construction diagonale particulièrement conçu pour les camions utilisés dans les opérations à l'intérieur des mines ou carrières. Chaque fois que vos conditions de travail pour les transports courts sur le site nécessitent à la fois résistance à la chaleur et protection contre les coupures, ROCK GRIP est le pneu qu'il vous faut.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Tombereau rigide

Version	STANDARD
Type	TL
Tyre Size	21.00 - 35

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	580
Overall Diameter (mm)	2040
Static Loaded Radius (mm)	943
Rolling Circumference (mm)	6068
Rim Rec	15.00/3.0
TRA Code	E4

## Load capacity (Kg)

km/h / bar	6.25	8.25
50	14000	-
10	-	24300

Printed on 27/04/2024 18:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..