

ROCK GRIP L4 - Spécifications techniques



Description

ROCK GRIP (L-4) est un pneu à construction diagonale pour les chargeuses sur pneus dans les opérations de chargement difficile sur terrains critiques. Le mélange spécial de la bande de roulement est particulièrement résistant à n'importe quel type de coupure, ce qui réduit le risque de crevaison et donc les temps d'arrêt machine. La profondeur (L-4) de la bande de roulement garantit un cycle de vie plus long du pneu.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Bulldozer • Chargeur

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

Dimensions US Standard

Usa code	94031214
Ply Rating	24
Overall Width (inch)	14.8
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	164.3
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (lbs)

mph / psi	123
5	20900

Printed on 27/04/2024 13:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..