

## ROCK GRIP L4 - Fiche de données



### Description

ROCK GRIP (L-4) est un pneu à construction diagonale pour les chargeuses sur pneus dans les opérations de chargement difficile sur terrains critiques. Le mélange spécial de la bande de roulement est particulièrement résistant à n'importe quel type de coupure, ce qui réduit le risque de crevaison et donc les temps d'arrêt machine. La profondeur (L-4) de la bande de roulement garantit un cycle de vie plus long du pneu.

### UM

International Standard

### Construction

✦ BIAS

### Machinery

Industriel: Bulldozer • Chargeur

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	32	10.00/1.5		375	1410	649	4173	TL

Printed on 27/04/2024 11:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..