

ROCK STAR IND4 - Spécifications techniques



Description

ROCK STAR PORT IND-4 a été spécialement conçu pour la manutention de conteneurs vides et des chariots élévateurs à fourche. Outre une excellente traction, la composition unique de la bande de roulement offre une résistance supérieure aux coupures et aux déchirures. ROCK STAR PORT IND-4 garantit une capacité de charge exceptionnelle et une durabilité hors du commun.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide • Chariot élévateur

| | |
|-----------|-----------------|
| Version | PORT INDUSTRIAL |
| Type | TT |
| Tyre Size | 14.00 - 24 |

Dimensions International Standard

| | |
|----------------------------|----------|
| Ply Rating | 28 |
| Overall Width (mm) | 390 |
| Overall Diameter (mm) | 1425 |
| Static Loaded Radius (mm) | 635 |
| Rolling Circumference (mm) | 4350 |
| Rim Rec | 10.00 WA |
| Rim Alt | 10.00 VA |
| TRA Code | IND4 |

Load capacity (Kg)

| | |
|------------|-------|
| km/h / bar | 10.00 |
| 10 | 13500 |

Printed on 03/02/2023 05:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..