

ROCK STAR (SB SPL) - Spécifications techniques



Description

ROCK STAR a été particulièrement conçu pour les moyens de transport tant sur route que sur des rails d'acier. ROCK STAR est un pneu à 32 plis pour une capacité de charge élevée. Le mélange unique de sa bande de roulement est particulièrement résistant aux coupures et déchirures alors que les ceintures en acier garantissent longévité.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Engin rail-route

Version	STEEL BELTED SPL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	390
Overall Diameter (mm)	1425
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 13:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..