RT 747 AGRO INDUSTRIAL - Spécifications techniques

Description

RT 747 AGRO INDUSTRIAL est un pneu radial agro-industriel adapté pour les chargeuses compactes et les chargeurs télescopiques. Les crampons extra larges assurent une excellente adhérence et une extraordinaire stabilité lors des opérations de levage. Le pneu a été développé avec un mélange résistant aux coupures et déchirures qui permet au pneu de supporter des charges lourdes. RT 747 AGRO INDUSTRIAL est la solution appropriée pour toutes les opérations agricoles en général qui demandent une grande polyvalence.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Chargeuse compacte • Chargeuse télescopique
Industriel: Chargeuse compacte • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	11L R 16
LI/SS	122 A8/B

Dimensions International Standard

Section Width (mm)	290
Overall Diameter (mm)	850
Rim Rec	W 8
Rim Alt	W 10 L
ECE	E11-106R-005769

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.2	2.4	2.6
10	1265	1530	1790	1920	2055	2200
30	940	1165	1385	1500	1610	---
40	880	1085	1295	1395	1500	---

Printed on 18/04/2024 01:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..