

RT 857 - Spécifications techniques



Description

RT 857 est un pneu qui convient pour les applications de travail de la terre. La carcasse robuste garantit une durabilité et une traction excellentes. Le mélange de la bande de roulement est caractérisé par une résistance élevée à tout type de coupure.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur

| | |
|-----------|----------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 320/85 R 28 (12.4 R 28) |
| LI/SS | 124 A8/B |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94041923 |
| Section Width (inch) | 13 |
| Overall Diameter (inch) | 49.4 |
| Static Loaded Radius (inch) | 22.7 |
| Rolling Circumference (inch) | 148.8 |
| Rim Rec | W 11 |
| Rim Alt | W 9 ; W 10 |
| ECE | E4-106R-000757 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 1940 | 2260 | 2580 | 2900 | 3220 | 3530 |
| 25 | 1940 | 2260 | 2580 | 2900 | 3220 | 3530 |
| 20 | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |
| 5 LT | 2600 | 3030 | 3460 | 3880 | 4310 | 4730 |
| 5 HT | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |

Printed on 25/04/2024 10:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..