

RT 857 - Spécifications techniques



Description

RT 857 est un pneu qui convient pour les applications de travail de la terre. La carcasse robuste garantit une durabilité et une traction excellentes. Le mélange de la bande de roulement est caractérisé par une résistance élevée à tout type de coupure.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TL
Tyre Size	460/85 R 26 (18.4 R 26)
LI/SS	143 A8/B

Dimensions US Standard

Usa code	94045624
Section Width (inch)	18.3
Overall Diameter (inch)	56.8
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	169.2
Rim Rec	DW 15 L
Rim Alt	W 15 L ; W 16 L ; DW 16 L
ECE	E4-106R-001479
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	3310	3850	4390	4930	5470	6010
25	3310	3850	4390	4930	5470	6010
20	3550	4120	4710	5280	5860	6440
5LT	4440	5160	5890	6610	7340	8060
5HT	3550	4120	4710	5280	5860	6440

Printed on 25/04/2024 10:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..