

SIERRA MAX PRO - Spécifications techniques



Description

Le pneu SIERRA MAX PRO de BKT est idéal pour les véhicules tout-terrain dans les applications ATV, y compris les courses côte à côte. Sa construction radiale et sa surface d'empreinte spéciale plus large permettent une conduite plus souple, ainsi qu'une traction latérale et avant optimisée. Des crampons spéciaux et solides ont été spécialement étudiés pour offrir une excellente traction et adhérence sur le terrain. Ces caractéristiques assurent une conduite remarquablement confortable, garantissant ainsi la sécurité et le contrôle de la conduite. Le SIERRA MAX PRO offre d'excellentes performances sur tous les types de terrain, des terrains durs aux sols meubles.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94066155
Section Width (inch)	11.2
Overall Diameter (inch)	27.9
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	84.4
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005098

Load capacity (lbs)

mph / psi	18
87	495

Printed on 27/04/2024 04:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..