# SIERRA MAX - Spécifications techniques

## Description

SIERRA MAX est le pneu BKT tant pour les applications ATV/VTT que pour les prés et jardins. Grâce à sa construction radiale, ce pneu offre une conduite beaucoup plus souple et confortable même sur des terrains extrêmement difficiles comme le désert ou les surfaces terreuses et rocheuses. Le dessin particulier de la bande de roulement et son empreinte plus large lui confèrent une traction antérieure et latérale incomparable.

## UM

US Standard

## Construction

RADIAL

## Machinery

Agriculture: Véhicule ATV

| | |
|---|---|
| **Version** | STANDARD |
| **Type** | TL |
| **Tyre Size** | AT 26 X 11 R 14 |
| **LI/SS** | 54 N |

## Dimensions US Standard

| | |
|---|---|
| **Usa code** | 94052332 |
| **Section Width (inch)** | 11 |
| **Overall Diameter (inch)** | 26.6 |
| **Static Loaded Radius (inch)** | 12.2 |
| **Rolling Circumference (inch)** | 79.8 |
| **Rim Rec** | 9.00 |
| **Star Rating** | *** |
| **ECE** | E11-75R-005096 |

## Load capacity (lbs)

| mph / psi | 7 |
|---|---|
| **87** | 465 |

Printed on 19/04/2024 10:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..