

## SKID POWER ( CHEVRON ) - Spécifications techniques



### Description

SKID POWER (CHEVRON) a été conçu pour les chargeuses compactes dans les applications de bâtiment. Faisant preuve d'une excellente traction et présentant des capacités élevées d'auto-nettoyage, SKID POWER (CHEVRON) est particulièrement adapté pour les surfaces terreuses, où il montre une grande résistance aux coupures et déchirures.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

Version	IMPLEMENT
Type	TL
Tyre Size	7.00 - 15
LI/SS	106 A8

## Dimensions US Standard

Usa code	94056118
Ply Rating	6
Section Width (inch)	8
Overall Diameter (inch)	30
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	90.4
Rim Rec	5.50 F
Rim Alt	6 LB
ECE	E11-106R-003583

## Load capacity (lbs)

mph / psi	60
25	2095

Printed on 23/04/2024 03:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..