

SKID POWER (CHEVRON) - Fiche de données



Description

SKID POWER (CHEVRON) a été conçu pour les chargeuses compactes dans les applications de bâtiment. Faisant preuve d'une excellente traction et présentant des capacités élevées d'auto-nettoyage, SKID POWER (CHEVRON) est particulièrement adapté pour les surfaces terreuses, où il montre une grande résistance aux coupures et déchirures.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.00 - 15	IMPLEMENT	94056118	106 A8	6	5.50 F	6 LB	8	30	13.7	90.4	TL	E11-106R-003583
7.00 - 15	STANDARD	94017171		6	5.50 F	6 LB	8	30	13.7	90.4	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/06/2025 05:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..