

SKID POWER HD (A) - Spécifications techniques



Description

SKID POWER HD (A) a été conçu pour les chargeuses compactes dans les applications de bâtiment. Ce pneu se distingue de par la bande de roulement extra profonde et la protection des flancs, qui lui confèrent une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER HD (A) est le pneu idéal pour les surfaces terreuses et les conditions pénibles.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

Version	IMPLEMENT
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	131 A8

Dimensions US Standard

Usa code	94057245
Ply Rating	12
Section Width (inch)	15.5
Overall Diameter (inch)	33
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	100.9
Rim Rec	13.00
ECE	E11-106R-003018

Load capacity (lbs)

mph / psi	60
25	4300

Printed on 06/05/2024 16:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..