

## SKID POWER PLUS - Spécifications techniques



### Description

SKID POWER PLUS a été conçu pour les chargeuses compactes dans les applications du bâtiment. Les barrettes plus larges garantissent une excellente traction ainsi que des propriétés d'autonettoyage exceptionnelles. Ce pneu se distingue de par la bande de roulement extra-profonde et par une meilleure protection des flancs, ce qui assure une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER PLUS est le pneu idéal pour les surfaces terreuses. La large zone de contact assure une stabilité optimale pendant les opérations.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

## Dimensions US Standard

Usa code	94054664
Ply Rating	8
Section Width (inch)	9.9
Overall Diameter (inch)	30.5
Rim Rec	8.25

## Load capacity (lbs)

mph / psi	60
5	4140
10	3270
15	3020

Printed on 26/04/2024 19:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..