

SKID POWER PLUS - Spécifications techniques



Description

SKID POWER PLUS a été conçu pour les chargeuses compactes dans les applications du bâtiment. Les barrettes plus larges garantissent une excellente traction ainsi que des propriétés d'autonettoyage exceptionnelles. Ce pneu se distingue de par la bande de roulement extra-profonde et par une meilleure protection des flancs, ce qui assure une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER PLUS est le pneu idéal pour les surfaces terreuses. La large zone de contact assure une stabilité optimale pendant les opérations.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur compact

Version	SPECIAL
Type	TL
Tyre Size	10 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	252
Overall Diameter (mm)	775
Rim Rec	8.25

Load capacity (Kg)

	km/h / bar	5.20
	10	2135
	15	1685
	25	1560

Printed on 26/04/2024 21:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..