

SL 441 - Spécifications techniques

Description

SL 441 est un pneu adapté pour le travail de la terre et les opérations de transport avec remorques et outils agricoles. SL 441 a été conçu pour offrir une capacité de charge élevée et un long cycle de vie.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Remorque



Version	STANDARD
Type	TL
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	278
Rolling Circumference (mm)	1785
Rim Rec	AG 6.75
ECE	E11-106R-003610

Load capacity (Kg)

	km/h / bar	7.00
	10 FR	1610
	25 FR	1370
	30 FR	1290
	40 FR	1150

Printed on 23/04/2024 14:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..