

## SM 53 - Spécifications techniques



### Description

SM 53 a été spécialement conçu pour les applications souterraines dans les mines et de chargement. Ce pneu est caractérisé par une grande stabilité et par une bande de roulement pleine, ce qui assure une excellente résistance aux coupures.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Véhicule miniers souterrains

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

## Dimensions International Standard

Ply Rating	16
Overall Width (mm)	266
Overall Diameter (mm)	1040
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3080
Rim Rec	7.0
TRA Code	L3S

## Load capacity (Kg)

	km/h / bar	7.25
	10	3965
	15	3450
	25	3170

Printed on 24/04/2024 09:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..