SM 53 - Fiche de données

Description

SM 53 a été spécialement conçu pour les applications souterraines dans les mines et de chargement. Ce pneu est caractérisé par une grande stabilité et par une bande de roulement pleine, ce qui assure une excellente résistance aux coupures.

UM

US Standard

Construction

BIAS

Machinery

OTR: Véhicule miniers souterrains

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
9.00 - 20	STANDARD	94041510	L3S	16	7.0		10.5	40.9	18.6	121.3	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/10/2024 04:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..