

SM 54 L4S - Spécifications techniques



Description

Le SM 54 (L-4S) a été spécialement conçu pour la manutention de conteneurs vides et les reach stackers dans les applications de transport intermodal et de logistique. Il se caractérise par une grande stabilité en mode de levage et une bande de roulement profonde et lisse, qui offre une excellente résistance aux coupures permettant ainsi de garantir une plus longue durée de vie aux pneus.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Reach stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94050208
Ply Rating	36
Overall Width (inch)	21.1
Overall Diameter (inch)	74.6
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	220.8
Rim Rec	13.00/2.5
TRA Code	L4S

Load capacity (lbs)

mph / psi	145
5	55100

Printed on 05/12/2023 18:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..