

SM 54 L4S - Fiche de données



Description

Le SM 54 (L-4S) a été spécialement conçu pour la manutention de conteneurs vides et les reach stackers dans les applications de transport intermodal et de logistique. Il se caractérise par une grande stabilité en mode de levage et une bande de roulement profonde et lisse, qui offre une excellente résistance aux coupures permettant ainsi de garantir une plus longue durée de vie aux pneus.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Reach stacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
16.00 - 25	INDUSTRIAL	94015610	L4S	28	11.25/2.0	13.00/2.0	16.9	57.9	26.6	171.4	TL
16.00 - 25	INDUSTRIAL	94015627	L4S	32	11.25/2.0	13.00/2.0	16.9	57.9	26.6	171.4	TL
18.00 - 33	PORT INDUSTRIAL	94050208	L4S	36	13.00/2.5		21.1	74.6	33.1	220.8	TL
18.00 - 33	PORT INDUSTRIAL	94050215	L4S	40	13.00/2.5		21.1	74.6	33.1	220.8	TL

Printed on 04/12/2023 18:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..