

SM 54 M IND-4S - Spécifications techniques



Description

SM 54 M IND-4S est la version modifiée du SM 54. La bande de roulement plus plat lui confère une zone de contact plus large qui assure un cycle de vie plus long. Le pneu a été particulièrement conçu pour les machines de manutention de conteneurs vides et pour les reach stackers dans les applications intermodales/logistiques. SM 54 M se distingue de par une grande stabilité en mode levage ainsi que par un dessin profond et lisse de la bande de roulement, qui confère une excellente résistance aux coupures.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Reach stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1650
Static Loaded Radius (mm)	750
Rolling Circumference (mm)	4880
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	L4S

Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 23/04/2024 17:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..