

SM 55 IND-5S - Spécifications techniques



Description

SM 55 IND-5S a été spécialement conçu pour les reach stackers et les unités de manutention de conteneurs. Son mélange spécial résistant à l'abrasion assure une vie plus longue du pneu sur des surfaces asphaltées ou cimentées, et offre aux engins une excellente stabilité lors des opérations de levage.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur

Version	PORT SPECIAL
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94039609
Ply Rating	40
Overall Width (inch)	20.4
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	201.5
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

Load capacity (lbs)

mph / psi	145
5	50625

Printed on 26/04/2024 10:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..