

SM 55 IND-5S - Fiche de données



Description

SM 55 IND-5S a été spécialement conçu pour les reach stackers et les unités de manutention de conteneurs. Son mélange spécial résistant à l'abrasion assure une vie plus longue du pneu sur des surfaces asphaltées ou cimentées, et offre aux engins une excellente stabilité lors des opérations de levage.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	PORT INDUSTRIAL	IND5	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT
18.00 - 25	PORT SPECIAL	IND5	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL

Printed on 26/04/2024 11:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..