

SM 55 L5S - Spécifications techniques



Description

SM 55 (L-5S) est un pneu à construction diagonale idéal pour les opérations souterraines dans les mines. La bande de roulement est réalisée dans un mélange spécial résistant aux coupures et déchirures, et est caractérisée par une profondeur extra L-5S. Ceci se traduit par des temps d'arrêt machine réduits, assurant ainsi une plus longue vie du pneu. Ce pneu est aussi disponible en version "steel belted" avec ceintures en acier.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Tombereau surbaissé • Véhicule miniers souterrains

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94053230
Ply Rating	32
Overall Width (inch)	20.4
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	201.5
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	L5S

Load capacity (lbs)

mph / psi	109
5	33100

Printed on 25/04/2024 23:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..