

## SM 55 L5S - Spécifications techniques



### Description

SM 55 (L-5S) est un pneu à construction diagonale idéal pour les opérations souterraines dans les mines. La bande de roulement est réalisée dans un mélange spécial résistant aux coupures et déchirures, et est caractérisée par une profondeur extra L-5S. Ceci se traduit par des temps d'arrêt machine réduits, assurant ainsi une plus longue vie du pneu. Ce pneu est aussi disponible en version "steel belted" avec ceintures en acier.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Tombereau surbaissé • Véhicule miniers souterrains

Version	STEEL BELTED
Type	TL
Tyre Size	26.5 - 25

## Dimensions US Standard

Usa code	94039951
Ply Rating	28
Overall Width (inch)	27.6
Overall Diameter (inch)	70.8
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	209.5
Rim Rec	22.00/3.0
TRA Code	L5S

## Load capacity (lbs)

mph / psi	69
5	34200
10	29700
15	27300

Printed on 25/04/2024 18:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..