

SM 55 L5S - Fiche de données



Description

SM 55 (L-5S) est un pneu à construction diagonale idéal pour les opérations souterraines dans les mines. La bande de roulement est réalisée dans un mélange spécial résistant aux coupures et déchirures, et est caractérisée par une profondeur extra L-5S. Ceci se traduit par des temps d'arrêt machine réduits, assurant ainsi une plus longue vie du pneu. Ce pneu est aussi disponible en version "steel belted" avec ceintures en acier.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Tombereau surbaissé • Véhicule miniers souterrains

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
7.00 - 12	DUAL BEAD	L5S	16	5.00 S		205	710	323	2159	TT	31
7.00 - 12	STANDARD	L5S	14	5.00 S		205	710	323	2159	TT	31
7.00 - 12	STANDARD	L5S	16	5.00 S		205	710	323	2159	TT	31
9.50 - 20	STANDARD	L5S	16	7.5		275	1065	505	3280	TT	58
12.00 - 24	STANDARD	L5S	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT	60
12.00 - 24	STANDARD	L5S	24	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT	60
12.00 - 24	STEEL BELTED	L5S	24	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT	60
17.5 - 25	ARASHIELD	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	438	1375	631	4043	TL	64
17.5 - 25	STANDARD	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	438	1375	631	4043	TL	64
17.5 - 25	STANDARD	L5S	20	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	438	1375	631	4043	TL	64
17.5 - 25	STEEL BELTED	L5S	20	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	438	1375	631	4043	TL	64
17.5 - 25	STEEL BELTED	L5S	24	14.00/1.5	14.00/1.3 ; 14.00/1.4 (DC)	438	1375	631	4043	TL	64
18.00 - 25	ARASHIELD	L5S	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
18.00 - 25	STANDARD	L5S	28	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
18.00 - 25	STANDARD	L5S	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
18.00 - 25	STANDARD	L5S	32	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
18.00 - 25	STEEL BELTED	L5S	28	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
18.00 - 25	STEEL BELTED	L5S	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL	83
20.5 - 25	STANDARD	L5S	20	17.00/2.0		530	1565			TL	80
26.5 - 25	ARASHIELD	L5S	36	22.00/3.0		700	1798	816	5322	TL	96
26.5 - 25	STEEL BELTED	L5S	28	22.00/3.0		700	1798	816	5322	TL	96
26.5 - 25	STEEL BELTED	L5S	32	22.00/3.0		700	1798	816	5322	TL	96
29.5 - 29	ARASHIELD	L5S	40	25.00/3.5	24.00/3.5	755	2020	882	6021	TL	104
29.5 - 29	STEEL BELTED	L5S	40	25.00/3.5	24.00/3.5	755	2020	882	6021	TL	104
29.5 - 29	STEEL BELTED	L5S	28	25.00/3.5	24.00/3.5	755	2020	882	6021	TL	104
35/65 - 33	ARASHIELD	L5S	48	28.00/3.5		920	2085	0	0	TL	98
35/65 - 33	STEEL BELTED	L5S	48	28.00/3.5		920	2085	0	0	TL	98
45/65 - 45	STEEL BELTED	L5S	58	36.00/4.5		1145	2750	0	0	TL	116

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/03/2025 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..