

SNOW - RIDE (B) - Spécifications techniques



Description

SNOW-RIDE est particulièrement adapté pour les applications sur route en conditions hivernales avec des chargeuses et bulldozers. Ce pneu se distingue de par une excellente traction et il est idéal pour les opérations sur la neige et la glace. Le dessin spécial de la bande de roulement élimine tout risque de dérapage.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Bulldozer • Chargeur

Version	STANDARD
Type	TL
Tyre Size	16.9 - 24

Dimensions International Standard

Ply Rating	12
TKPH	1
Section Width (mm)	429
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3930
SRI (mm)	625
Rim Rec	DW 15 L
Rim Alt	DW 14 L

Load capacity (Kg)

km/h / bar	2.60
40	3250

Printed on 17/04/2024 05:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..