

SR 713 - Spécifications techniques



Description

SR 713 est un pneu radial **All Steel** (Tout Acier) doté de la technologie VF pour engins agricoles. Ce pneu est caractérisé par une carcasse robuste avec ceintures en acier multicouches et par une bande de roulement au dessin à rainures multiples qui garantissent une faible résistance au roulement ainsi qu'une usure uniforme de la bande de roulement. Grâce à son empreinte large, ce pneu VF assure un compactage réduit du sol. SR 713 se distingue tant en termes de performances que par sa fiabilité, tout en offrant d'excellents niveaux de vitesse même sur la route.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Outillage agricole

| | |
|-----------|------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | VF 295/75 R 22.5 |
| LI/SS | 151 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Overall Width (mm) | 280 |
| Overall Diameter (mm) | 1020 |
| Static Loaded Radius (mm) | 449 |
| Rolling Circumference (mm) | 3044 |
| Rim Rec | 9.00 |
| Rim Alt | 8.25 |
| ECE | E11-106R-005500 |
| TRA Code | I1 |

Load capacity (Kg)

| km/h / bar | 2.4 | 2.6 | 2.8 | 3 | 3.2 | 3.4 | 3.6 | 3.8 | 4 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 0 | 4875 | 5150 | 5590 | 5920 | 6095 | 6265 | 6670 | 6900 | 7245 | 7705 | 7935 |
| 10 | 3815 | 4030 | 4375 | 4635 | 4770 | 4905 | 5220 | 5400 | 5670 | 6030 | 6210 |
| 15 | 3670 | 3875 | 4205 | 4455 | 4585 | 4715 | 5015 | 5190 | 5450 | 5795 | 5970 |
| 25 | 3350 | 3540 | 3840 | 4070 | 4185 | 4305 | 4580 | 4740 | 4975 | 5295 | 5450 |
| 30 | 3200 | 3380 | 3670 | 3890 | 4000 | 4115 | 4380 | 4530 | 4755 | 5060 | 5210 |
| 40 | 2885 | 3045 | 3305 | 3500 | 3605 | 3705 | 3945 | 4080 | 4285 | 4555 | 4690 |
| 50 | 2565 | 2710 | 2940 | 3115 | 3205 | 3295 | 3510 | 3630 | 3810 | 4055 | 4175 |
| 60 | 2270 | 2395 | 2600 | 2755 | 2835 | 2915 | 3105 | 3210 | 3370 | 3585 | 3690 |
| 65 | 2120 | 2240 | 2430 | 2575 | 2650 | 2725 | 2900 | 3000 | 3150 | 3350 | 3450 |
| 70 | 1930 | 2040 | 2210 | 2345 | 2410 | 2480 | 2640 | 2730 | 2865 | 3050 | 3140 |

Printed on 26/04/2024 08:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..