

## ST 180 - Fiche de données



### Description

ST 180 est un pneu essentiellement utilisé sur la route, conçu pour les applications de transport avec remorques et outils agricoles. Le dessin spécifique de la bande de roulement réduit l'usure, garantissant un long cycle de vie du pneu. ST 180 est disponible en plus versions: une version « aramid belted », avec ceintures en aramide, pour donner une plus grande résistance aux perforations, tandis que la version spécial « special » assure une résistance élevée aux coupures et déchirures.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Outillage agricole • Remorque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.80 - 8	STANDARD	6	3.75 - I - 55	3.75 - I - 70	121	418	0	0	TL	
5.70 - 8	STANDARD	8	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	142	475	0	0	TL	
5.70 - 8	STANDARD	6	4.50 - I - 55	I - 70 ; I - 90 ; 3.75	142	475	0	0	TL	
6.00 - 9	STANDARD	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	165	540	0	0	TT	E4-54R-0022804
6.00 - 9	STANDARD	8	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	165	540	0	0	TL	E4-54R-0022804
6.00 - 9	STANDARD	10	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	165	540	0	0	TL	E4-54R-0022805
6.00 - 9	STANDARD	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	165	540	0	0	TT	E4-54R-0022806
6.00 - 9	STANDARD	12	4.00 - I - 55	4.50 - I - 55 ; I - 70 ; I - 90	165	540	0	0	TL	E4-54R-0022806
5.00 - 10	STANDARD	6	3.5		142	530	0	0	TL	E4-54R-0030484
ST 165/80 D 13 (A 78 - 13)	STANDARD	4	4½ J	5 J ; 5½ J ; 6 J	156	597	272	1746	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	4	5 J	4½ J ; 5½ J ; 6 J	175	620	286	1845	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	6	5 J	4½ J ; 5½ J ; 6 J	175	620	286	1845	TL	
ST 175/80 D 13 (B 78 - 13)	STANDARD	8	5 J	4½ J ; 5½ J ; 6 J	175	620	286	1845	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	4	5 J	5½ J ; 6 J ; 6½ J	192	668	312	2013	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	6	5 J	5½ J ; 6 J ; 6½ J	192	668	312	2013	TL	
ST 195/75 D 14 (E 78 - 14)	STANDARD	8	5 J	5½ J ; 6 J ; 6½ J	192	668	312	2013	TL	
ST 205/65 D 14 (F 65 - 14)	STANDARD	6	5 J	5½ J	190	621	292	1875	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	4	6 J	5 J ; 5½ J ; 6 J	200	682	317	2049	TL	
ST 205/75 D 14 (F 78 - 14)	STANDARD	6	6 J	5 J ; 5½ J ; 6 J	200	682	317	2049	TL	
ST 215/75 D 14 (G 78 - 14)	ARAMID BELTED	10	6 J	5½ J ; 6½ J ; 7 J	205	682	320	2073	TL	
ST 215/75 D 14 (G 78 - 14)	SPECIAL	10	6 J	5½ J ; 6½ J ; 7 J	205	682	320	2073	TL	
ST 215/75 D 14 (G 78 - 14)	STANDARD	6	6 J	5½ J ; 6½ J ; 7 J	205	682	320	2073	TL	
ST 205/65 D 15 (F 65 - 15)	STANDARD	6	6 J	5½ J ; 6½ J	193	648	303	1935	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	4	5½ J	5 J ; 6 J ; 7 J	195	702	327	2103	TL	
ST 205/75 D 15 (F 78 - 15)	STANDARD	6	5½ J	5 J ; 6 J ; 7 J	195	702	327	2103	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	6	6 J	5½ J ; 6½ J ; 7 J	217	730	337	2178	TL	
ST 225/75 D 15 (H 78 - 15)	STANDARD	8	6 J	5½ J ; 6½ J ; 7 J	217	730	337	2178	TL	

Printed on 25/04/2024 10:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part,

