

## STAR TRAC - Spécifications techniques



### Description

STAR TRAC est le pneu BKT pour faucheuses dans les plantations de coton, en mesure de supporter de lourdes charges. Grâce au dessin de la bande de roulement particulièrement profond, ce pneu assure une excellente traction dans les champs ainsi que des performances optimales pendant les transferts sur route. Dans les plantations de coton où l'on trouve des buissons généralement de moyennes dimensions, les opérations de récolte demandent au pneu d'avoir d'excellentes capacités de flottaison ainsi qu'un moindre compactage du sol. De plus, ce pneu a été réalisé dans un mélange spécial qui lui confère une grande résistance contre les coupures et les dommages typiques de cette application.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Machine à récolter le coton

Version	STANDARD
Type	TL
Tyre Size	DW 500/95 D 32
LI/SS	162 A8/169 A5

## Dimensions US Standard

Usa code	94041404
Section Width (inch)	19.7
Overall Diameter (inch)	72.3
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	209.6
Rim Rec	13.00 DW

## Load capacity (lbs)

mph / psi	26
25	10470
15	12790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 14:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..