

SUPER GRADER - Spécifications techniques



Description

SUPER GRADER (G-2) est un pneu diagonal particulièrement conçu pour les niveleuses, qui fait preuve d'une excellente traction et d'une grande capacité d'auto-nettoyage. SUPER GRADER a été réalisé dans un mélange spécial qui permet d'avoir un cycle de vie plus long du pneu et d'être utilisé pour des services pénibles.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Niveleuse

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

Dimensions US Standard

Usa code	94035335
Ply Rating	16
Overall Width (inch)	13.4
Overall Diameter (inch)	50.2
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	149.6
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
TRA Code	G2

Load capacity (lbs)

mph / psi	58
25	7140

Printed on 19/04/2024 19:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..