

SUPER SAND - Spécifications techniques



Description

SUPER SAND est particulièrement adapté pour les remorques qui opèrent sur des surfaces sableuses dans des conditions climatiques de chaleur. Ce pneu se distingue de par une grande capacité de flottaison et il est idéal pour toutes les opérations qui demandent un niveau de maniabilité élevé.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16

Dimensions US Standard

Usa code	94014279
Ply Rating	8
Section Width (inch)	10
Overall Diameter (inch)	34.8
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (lbs)

mph / psi	35
40 LS	2150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 15:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..