

## TERRA TRAX - Spécifications techniques



### Description

TERRA TRAX a été spécialement conçu pour les outils de fourrage. Ce pneu est approprié tant pour une utilisation sur route que hors route. TERRA TRAX assure de bonnes performances sur route ainsi que d'excellentes qualité de confort de conduite et d'autonettoyage. La faible résistance au roulement contribue à réduire la consommation de carburant.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5
LI/SS	156 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	395
Overall Diameter (mm)	785
Static Loaded Radius (mm)	361
Rolling Circumference (mm)	2370
Rim Rec	14.00
ECE	E11-106R-006002

## Load capacity (Kg)

km/h / bar	6.00
40	4000

Printed on 30/11/2023 14:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..