

TERRA TRAX - Spécifications techniques



Description

TERRA TRAX a été spécialement conçu pour les outils de fouflage. Ce pneu est approprié tant pour une utilisation sur route que hors route. TERRA TRAX assure de bonnes performances sur route ainsi que d'excellentes qualité de confort de conduite et d'autonettoyage. La faible résistance au roulement contribue à réduire la consommation de carburant.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole

Version	STANDARD
Type	TL
Tyre Size	400/45L - 17.5

Dimensions US Standard

Usa code	94063451
Ply Rating	14
Section Width (inch)	15.6
Overall Diameter (inch)	30.9
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	93.3
Rim Rec	14.00
ECE	E11-106R-006002

Load capacity (lbs)

mph / psi	87
25	8800

Printed on 26/04/2024 00:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..