

TF 9090 - Spécifications techniques



Description

TF 9090 est un pneu conçu pour les micro tracteurs dans les opérations de travail de la terre. Le dessin spécial de la bande de roulement offre un excellent braquage sur le sol meuble.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Micro tracteur
Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	4.00 - 19
LI/SS	72 A6

Dimensions International Standard

Ply Rating	4
Section Width (mm)	115
Overall Diameter (mm)	715
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2145
Rim Rec	3.00 D
ECE	E11-106R-003355
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.40
30	355

Printed on 11/12/2023 03:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..