

TR 128 - Fiche de données



Description

TR 128 a été particulièrement conçu pour les tracteurs compacts et les rotoculteurs. Le dessin large et profond des pavés ainsi que le mélange particulièrement résistant aux coupures et déchirures assurent une plus longue vie du pneu. TR 128 se distingue de par une traction optimale sur terrains mouillés.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Rotoculteur • Véhicule universel

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
180/85 D 12	STANDARD	63 A6	4	5 JA		165	612	295	1847	TT	E11-106R-004821
180/85 D 12	STANDARD	76 A6	6	5 JA		165	612	288	1847	TT	E11-106R-005207
5 - 12	STANDARD		4	4 JA		127	554	262	1700	TT	E11-106R-003477
5 - 12	STANDARD	64 A6	6	4 JA		127	554	262	1700	TT	E11-106R-005189
6.00 - 12	STANDARD	69 A6	4	4.00 E	4.00 E DT	160	635	296	1926	TT	E11-106R-003478
6.00 - 12	STANDARD	76 A6	6	4.00 E	4.00 E DT	160	635	296	1926	TT	E11-106R-003479
6.00 - 12	STANDARD	82 A6	8	4.00 E	4.00 E DT	160	635	296	1926	TT	
7 - 14	STANDARD	95 A6	8	5 JA	5 J	173	690	323	2086	TT	E11-106R-004093

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 14/02/2025 15:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..