



## TR 133 - Fiche de données



### Description

TR 133 a été spécialement conçu pour les tracteurs dans les applications de travail de la terre. Grâce au nombre plus élevé des pavés, ce pneu se distingue de par une excellente traction et des propriétés d'auto-nettoyage élevées. TR 133 garantit un cycle de vie plus long du pneu.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Tracteur

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>13.6 - 38 (14.00 - 38)</b>	STANDARD	94043897	R1	132 A8	10	W 12	W 11	13.8	62.2	28.9	190.7	TT	E11-106R-003549

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 12:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..