

TR 137 - Spécifications techniques



Description

TR 137 est le pneu le plus adapté de BKT pour toutes les opérations de récolte, car il fait preuve d'une excellente traction dans les champs même avec des charges élevés. Ce pneu est disponible en différentes versions: la version "aramid-belted", avec ceintures en aramide, offre une meilleure résistance aux perforations et une bonne protection contre tous les dommages caractéristiques de cette application; la version "HD" offre une résistance extraordinaire aux coupures et déchirures ainsi qu'un cycle de vie du pneu long.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Moissonneuse

| | |
|-----------|------------|
| Version | HD |
| Type | TL |
| Tyre Size | 30.5L - 32 |
| LI/SS | 167 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94004355 |
| Ply Rating | 18 |
| Section Width (inch) | 30.3 |
| Overall Diameter (inch) | 73.4 |
| Static Loaded Radius (inch) | 32.7 |
| Rolling Circumference (inch) | 217.3 |
| Rim Rec | DH 27 B |
| Rim Alt | DW 27 B |
| ECE | E4-106R-002283 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 30 |
| 25 | 12010 |

Printed on 26/04/2024 05:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..