

## TR 144 - Spécifications techniques



### Description

TR 144 est adapté pour être utilisé sur les micro tracteurs dans les opérations de travail de la terre. TR 144 garantit des performances exceptionnelles dans toutes les conditions opérationnelles qui demandent une excellente traction associée à de charges élevés. Le pneu est aussi disponible en version « special », tout à fait appropriée aux opérations de service pénible.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TT
Tyre Size	8 - 18
LI/SS	94 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	195
Overall Diameter (mm)	835
Static Loaded Radius (mm)	385
Rolling Circumference (mm)	2509
Rim Rec	W 6
Rim Alt	W 7 ; 5.50 F
ECE	E11-106R-006467
TRA Code	R1

## Load capacity (Kg)

km/h / bar	1.90
30	670

Printed on 26/04/2024 20:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..