

## TR 145 - Spécifications techniques



### Description

TR 145 a été spécialement conçu pour les tracteurs de petite taille. Le dessin particulier de la bande de roulement offre d'excellentes traction et capacité d'auto-nettoyage. Le dessin large et profond des pavés assure une plus longue vie du pneu. TR 145 bénéficie d'une zone de contact large qui lui confère un confort de conduit extraordinaire et une stabilité directionnelle élevée.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TT
Tyre Size	160/90 - 12
LI/SS	72 A8

## Dimensions US Standard

Usa code	94062744
Ply Rating	6
Section Width (inch)	6.3
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	77.5
Rim Rec	4.00
ECE	E11-106R-005854
TRA Code	R1

## Load capacity (lbs)

mph / psi	36
2	785

Printed on 26/04/2024 21:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..